

∞ Infinity ACL

9147



SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- UV effect
- 7 rotating aerial effects + open
- Beam Angle 6°
- Iris
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 612 mm (24.1 in), head straight up
- Weight: 22.5 kg (49.6 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 300/2 FastFit
- Color temperature: 8000 Kelvin
- Color rendering index: 75
- Average lamp life: 750 hours
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 18
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 2 A at 230 V, 4.4 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- RJ45 for upload and remote control

KEY FEATURES

- **Brighter than a 1200 W fixture, in a 250 W package**
- **Focuseable black-light**
- **Variable beam size**
- **Variable beam control with rotating aerial effects**
- **Included moon flower effect**
- **Split color beam effects**

