

∞ Infinity Spot S

9143



SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- 1 aerial wheel, 7 gobos + open
- 1 break-up wheel, 7 gobos + open
- 3 rotating prisms
- Focus
- Proportional zoom 8,5° - 35°
- Iris
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 602 mm (23.7 in), head straight up
- Weight: 23.5 kg (51.8 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 300/2 FastFit
- Color temperature: 8000 Kelvin
- Color rendering index: 75
- Average lamp life: 750 hours
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 24
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 2 A at 230 V, 4.4 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- RJ45 for upload and remote control

KEY FEATURES

- **Bright as a 575 W fixture, in a package half the size**
- **Replace both 575 and 250 spot fixtures with one fully equipped moving light**
- **Space, weight, power saving**
- **Amazing zoom range from 35° down to 8,5°**
- **Silent operation for the quietest applications**
- **Iris and all other professional features**
- **Rotating and indexing prism effects**

