

∞ Infinity Spot XL

9137



KEY FEATURES

- **7° to 50° zoom**
- **Ground breaking new color mix system able to achieve CMY and RGB colors (CMY-s®, Exclusive Coemar Patent)**
- **Maximum exploitation of the new 1500 W light source, brightness never achieved before**
- **Unique variety of effect generated**

SPECIFICATIONS

- CMY-s® color mixing system with new saturation mode (**Exclusive Coemar Patent**)
- 5 colors + open
- Proportional CTO
- 1 aerial wheel, 6 rotating gobos + open
- 1 break-up wheel, 6 rotating gobos + open
- 1 effect wheel, for rotating prisms and gobo effects, 6 + open
- Focus
- Proportional zoom 7°- 50°
- Iris
- Dimmer
- Mechanical strobe, electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 530°, Tilt 270°, 16 bit

PHYSICAL SIZE

- Length: 450 mm (17.7 in)
- Width: 505 mm (19.9 in)
- Height: 880 mm (30.7 in), head straight up

- Weight: 51 kg (112.4 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 1500 Fast Fit
- Color temperature: 6000 Kelvin
- Color rendering index: 83
- Average lamp life: 750 hours
- Socket: PGJX50
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 34
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 8 A at 230 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- RJ45 for upload and remote control

