

# ∞ Infinity Spot M



## KEY FEATURES

- **“MULTI-lamp” concept ready**
- **Amazing linear fast zoom range from 42° down to 9°**
- **Bright as a 1200 W fixture, in a package 1/3 the size and 60% of the power**
- **Space, weight, power saving**
- **Fully equipped effects engine**
- **Artnet control protocol**

## SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- 1 aerial wheel, 7 gobos + open
- 1 break-up wheel, 7 gobos + open
- 2 rotating prisms
- Film frame effect
- Focus
- Proportional zoom 9° - 42°
- Proportional frost
- Iris
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

## PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 602 mm (23.7 in), head straight up
- Weight: 24 kg (52.9 lbs)

## LAMP AND BALLAST

- Type: Philips MSR Gold 700/2 Mini FastFit, MULTI-lamp ready
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

## CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet
- DMX channels: 24
- Setting and addressing: LCD display or via DR 1 + (allows replication of all display functions remotely via bidirectional DMX 512 and software upgrades)

## ELECTRICAL

### SPECIFICATIONS/CONNECTIONS

- AC power: 90 – 260 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: max 700W= 4,5 A at 230 V, 9,5 A at 115 V  
cos  $\phi$  = 0,9
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port