# SolaWash 2000



SolaWash 2000 is the next step in the bright white LED revolution from High End Systems.

With incredible output from a 600w LED source, there is now a wash light with no compromises. The SolaWash 2000 is the only LED wash light able to outshine 1500w metal halide units while using half the power and reducing maintenance intervals and operating costs. The fixture also comes with a 2 year warranty as standard.

Packed with CMY, Variable CTO, 2 Fixed Color Wheels, Framing, Iris, 2 variable Wash Filters, a 9 to 51 degree zoom range and the ability to create stunning beam looks, this is a true workhourse of any rig.

Complementing this full feature set, the SolaWash 2000 includes High End Systems' patented thermal contol software, ensuring that the fisture's cooling system is as efficient as possible while being whisper quiet. Further to this, there are various cooling modes in order to meet differing customer requirements such as opera and broadcast.

Alongside the SolaSpot Pro 2000, SolaSpot Pro 1500 and the SolaSpot Pro CMY, the SolaWash 2000 rounds off the brightest, most feature-rich and complete range of LED moving lights available!

#### **FEATURES**

LED Type	600 W Bright White Engine
Lumens	> 26,000*
LED Hours	> 50,000
СМҮ	Yes
Linear CTO	Yes
Fixed Color Wheel 1	6 + Open
Fixed Color Wheel 2	6 + Open
Framing System	Yes
Zoom – Wash Mode	9 to 51 degrees
Zoom – Beam Mode	5.5 to 42 degrees
<b>Active Thermal Con</b>	trol Yes
RDM Compatible	Yes
Roadcase included	Single

## **Operation**

Auto Switching Power Supply	Yes
5 Pin DMX/ RDM Connector	Yes
3 Pin DMX Connector	Yes
Powercon Connector	Yes

#### Construction

Modular Construction	Yes
Fast Service Design	Yes
Electronic Cooling System Control	Yes
Pan and Tilt Locks	Yes
Integrated Yoke Arm Handles	Yes

## **Electrical / Physical / Compliance**

Electrical	100-240VAC @ 50-60Hz	
Compliance		ETL, CE
Fixture Dimensions (inc	hes) 18.5 x 1	2.6 x 34.9
Fixture Dimensions (m	n) 475	x320x886
Fixture Weight (lbs)		92
Fixture Weight (kg)		41
Road Case Dimensions	(inches) 32	x 22 x 40
Road Case Dimensions	(mm) 764x	559x1016
Road Case Gross Weig	nt (lbs)	184
Road Case Gross Weig	nt (kg)	84



Patents Pending Specifications Subject to Change Without Notice Two year product warranty and technical support

