

EclDisplay CCFC

40W RGB+WW LED gallery light, Tunable White and Full Colour, constant current to be connected to external PSU & Driver



EclDisplay CCFC
+
ECLDISPPRZL2040 (optional)



EclDisplay CCFC
+
ECLDISPWASH1530 (optional)



40W RGB + Warm White LED



Constant current external driver



NO electronic on board



(Wash lens - optional) 15° ~ 30° / 25° ~ 50° manual



(Profile lens - optional) 20° ~ 40° manual



Shutter blades lockable (profile lens only)



360° rotation of lens and framing system



360° rotating barndoors and gel frame holder



Lockable tilt with screw



Hanging / ceiling installation



IP 20 for indoor use



RAL 9004 (black standard) - RAL 9010 (white standard)



RAL custom (colour on demand)



European Conformity certification



Check the website for detailed specifications and tech

EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application.

The **EclDisplay CCFC** is the version of the **EclDisplay** range made to be connected to an external Constant Current PSU and driver (max 4 x 1.4A/4.5V), selecting among the PROLIGHTS accessories or any third-party compatible component, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. **EclDisplay CCFC** includes a high-efficiency 40W RGB + Warm White LED capable of delivering both a Full Colour spectrum and also tuneable White, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture.


MAIN FEATURES

- Constant Current version to be connected to external PSU and driver (max 4 x 1.4A/4.5V)
- 40W RGB + Warm White LED capable to deliver both a Full Colour generation and also Tunable White
- Multiple lens options: zoomable profile or wash optics

VERSIONS

Code	Housing
ECLDISPLAYCCFCB	Black
ECLDISPLAYCCFCW	White


Track installation
with **Nordic Aluminium** accessories



Hanging installation
with **Protruss** accessories



Ceiling installation
with **Ceiling kit** accessories



PRODUCT SPECIFICATIONS

LIGHT SOURCE

- Source: 40W RGB + Warm White LED
- Luminous flux: (profile - 20°) 366 lm - (profile - 40°) 325 lm; (wash 2550 - min) 308 lm - (wash 2550 - max) 407 lm; (wash 1530 - min) 309 lm - (wash 1530 - max) 343 lm @full
- Lux: (profile - 20°) 194 lx - (profile - 40°) 42lx; (wash 2550 - min) 49 lx - (wash 2550 - max) 20 lx; (wash 1530 - min) 119 lx - (wash 1530 - max) 58 lx @5 m full
- Source life expectancy: > 50.000 hrs (L70B10 @Ta 25° C / 77° F)

OPTICS

- Zoom: (wash lens - optional) 15° ~ 30° or 25° ~ 50° - (profile lens - optional) 20° ~ 40°
- Other: 360° lens rotation - shutter blades lockable - optional 360° rotating barndoors and gel frame holder
- Other: (profile lens) shutter blades lockable
- Other: (profile lens - optional) manual rotating gobo holder size E, outer: 37 mm - image: 23 mm - thickness: max 3 mm

COLOUR SYSTEM

- Colour mixing: RGB + Warm White

BODY

- Hardware on-board: lockable tilt with screw
- Body: aluminium die-casting
- Body colour: RAL 9004 or RAL 9010
- Other: 1m cable included - Cable diameter range: 6 - 10 mm

ELECTRICAL

- Constant Current mains: max 4 x 1.4A/4.5V
- Max power consumption: 30W




















PHYSICAL

- Operating Temperature: -10° ~ +45°
- IP rating: 20
- Cooling: passive cooling and fan-free
- Suspension and fixing: hanging / ceiling installation
- Data: screw terminal blocks
- Dimensions (WxHxD): 124X200x150 mm
- Weight: 1,15 kg

TECHNICAL DRAWINGS

<p>Weight: 1.38 kg - 3.04 lbs</p> <p>ECLDISPLAYCCFC with ECLDISPWASH1530</p>	<p>ECLDISPWASH1530</p>	<p>ECLDISPBDNFF</p>	
<p>Weight: 1.36 kg - 3.01 lbs</p> <p>ECLDISPLAYCCFC with ECLDISPWASH2550</p>	<p>ECLDISPWASH2550</p>	<p>ECLDISPHSNOOT</p>	
<p>Weight: 1.55 kg - 3.41 lbs</p> <p>ECLDISPLAYUCCFC with ECLDISPPRZL2040</p>	<p>ECLDISPPRZL2040</p>	<p>ECLDISPFSNOOT</p>	
<p>ECLDISPCEILKIT</p>	<p>ECLDISPCEILFLG</p>	<p>ECLDISPLOUVRE</p>	<p>ECLDISPGOBOHND</p>

ACCESSORIES

IMAGE	CODE	DESCRIPTION	IMAGE	CODE	DESCRIPTION
	ECLDISPWASHL1530B	Zoomable Wash Lens 15-30° for EclDisplay, black housing		ECLDISPLOUVREB	Anti-glare louvre for EclDisplay, black housing
	ECLDISPWASHL1530W	Zoomable Wash Lens 15-30° for EclDisplay, white housing		ECLDISPLOUVREW	Anti-glare louvre for EclDisplay, white housing
	ECLDISPWASHL2550B	Zoomable Wash Lens 25-50° for EclDisplay, black housing		ECLDISPBDNFFB	Barndoor and filter frame (compatible with Wash Lenses) for EclDisplay, black
	ECLDISPWASHL2550W	Zoomable Wash Lens 25-50° for EclDisplay, white housing		ECLDISPBDNFFW	Barndoor and filter frame (compatible with Wash Lenses) for EclDisplay, white
	ECLDISPPRZL2040B	Zoomable Profile Lens 20-40°, with 4 framing shutters, for EclDisplay, black housing		ECLDISPGOBOHINDB	Gobo holder for EclDisplay with manual index gear on board, black
	ECLDISPPRZL2040W	Zoomable Profile Lens 20-40°, with 4 framing shutters, for EclDisplay, white housing		ECLDISPGOBOHINDW	Gobo holder for EclDisplay with manual index gear on board, white
	ECLDISPHSNOOTB	Half Snoot for EclDisplay, black housing		ECLDISPCEILKIT	Ceiling adapter kit for EclDisplay (without flange)
	ECLDISPFSNOOTB	Full Snoot for EclDisplay, black housing		ECLDISPCEILFLGB	Black flange to complete the EclDisplay ceiling adapter kit, black
	ECLDISPHSNOOTW	Half Snoot for EclDisplay, white housing		ECLDISPCEILFLGW	White flange to complete the EclDisplay ceiling adapter kit, white
	ECLDISPFSNOOTW	Full Snoot for EclDisplay, white housing			

ORDERING INFORMATION

MODEL	COLOUR TEMP	HOUSING	LENS TYPE	OPTICAL ACCESSORIES	DRIVER & CONNECTION	CEILING INSTALLATION
ECLDISPLAYCC	FC (RGB + WW)	BK (black housing) WH (white housing)	ECLDISPWASHL1530 (15°-30° wash lens) ECLDISPWASHL2550 (25°-50° wash lens) ECLDISPPRZL2040 (20°-40° profile lens)	ECLDISPHSNOOT (half snoot) ECLDISPFSNOOT (full snoot) ECLDISPLOUVRE (anti-glare louvre) ECLDISPBDNFF (barndoor + filter frame) ECLDISPGOBOHIND (gobo holder)	ELPD50SAM4Z0X (EldoLED power drive DMX-RDM) ELTOOLBOXPRO (EldoLED tool box)	ECLDISPCEILKIT (ceiling installation kit) ECLDISPCEILFLG (ceiling installation flange)