









MINI-B

THE TINY MEMBER OF THE B-EYE FAMILY WITH A BIG STING!

Mini-B is the smallest LED beam light ever made by Claypaky for the professional market.

Although it weighs just 6.5 Kg (14.3 pounds) and measures only 34 cm (13.4 inches), Mini-B features the most modern optical and electronic technology. The light source is based on 40 Watt Osram RGBW LEDs, the same ones fitted in the new Claypaky HY B-EYE. These LEDs, combined with a Claypaky optical unit including a collimator and seven external lenses, produce a highly efficient light output with very low power consumption. Thanks to its compact size and light weight, the pan and tilt movements can be driven at exceptionally high speed

and used to create exciting moving light effects, which are particularly useful at rock concerts.

Mini-B features a wide zoom, ranging from 4° to 55°, that makes this little luminaire extremely versatile. At the narrow angle, the beam produced is very solid and concentrated, superb for aerial effects. At full aperture, the Mini-B becomes an excellent wash light and it can replace much heavier and bulkier equipment, on stages, in TV studios, at multi-purpose venues and at clubs.

Thanks to its **competitive price**, Lighting Designers can afford to deploy as many Mini-B as they like to create amazing shows.



The Mini-B's central LED may be controlled separately from the external ring of LEDs, making it ideal for graphic lighting effects too. More than fifty pre-installed effects/color macros, 2500K-8000K color temperature control, a 16 bit dimmer with four curves, an electronic strobe @ 25 f/sec, and Ethernet access complete this highly professional tool.

MAIN FEATURES

- Light Source: 7 x RGBW Osram Ostar LEDs
- LED power rating: 40 W
- Extremely compact and lightweight
- Highly efficient light output, very low power consumption
- Very high-speed Pan and Tilt movements
- 4°-55° Zoom range
- Independent control of the central LED
- Pre-installed effects/color macros
- 2500K 8000K color temperature control
- 16 bit dimmer with 4 curves
- Electronic strobe @ 25 f/sec
- Ethernet access

WEIGHT AND DIMENSIONS

6.5 Kg (14.3 lbs)

224Mm x 186mm x 340mm (8.8" x 7.3" x 13.4")